7KH VRIWZDUH IRU 0DLQ%RVV $GYDQFHG GRHVQ¶W KDYH W

Below we list the recommended order of operations for installae ammaa

Scopes: In the procedure described below, you record the login names of people authorized to

4.

Automatically Create Requestors, **Automatically Create Requestors From Active Directory**, **Automatically Create Requestors From Email**

DQ³Email´ ILHOG PDWFKLQJ WKH HPDLO DGGUHVV RI W
request. If so, MainBoss Service creates a requestor record referring to that

\RX¶YH FRPSOHWHG You may also want to blank out the box if you

do so.

Notification Interval

Note: Before MainBoss 4.0, a different system was used to customize the contents of email

4. On the second dropdown button at the bottom of the screen, click

message strings you can customize. Click on one, then click

opens the database that has the organization name `myOrganization`.

Start Modes on the MainBoss Command Line

The command line lets you specify a particular *mode*

4.

(By default, SQL Server puts backup files on the same disk as the corresponding database.

Backup

Abbreviations on the MBUtility Command Line: Most keywords on the MBUtility command line may be abbreviated. In the sections that follow, letters that *must* be included are

`+OrderbyDatabaseName`
Sorts the list by database name.

```
mbutility AddOrganization option option ...
```

where the options are:

`+Replace`

`+PreservePrimaryEmailAddress`

Preserves the primary email addressI R U V H O H F W H G F R Q W D F W U H F R U G V
2 W K H U Z L V H W K H F R Q W D F W U H F R U G ¶ V S U L P D U \ H P D L O D

`UpdateAll`

imary email addres fpretimerery.

s o all contar A#]*Ë£jËî¿A/ 6–˜" D W K Z L @ °

Using SQL Server to Restore a Database from Backup

To restore a database from a backup file, follow these steps:

1.

If you ever intend to have multiple MainBoss users, we offer the following suggestions as options to choose during installation. Your site might decide to make different choices, but our suggestions should help typical users find their way through the many possibilities.

Unless otherwise stated below, we recommend that you accept the defaT/ t (opto(n)3(sinf)-6)]TETBT1 0 0

Appendix B: Troubleshooting

checking potential sources of difficulty. All of these tests use standard Microsoft software. If the tests fail somewhere, you can hope the software provide

4.

```
ipconfig
```

The list of protocols also offers the possibility of enabling SQL Server access through named

Adjusting the Firewall

In order for other computers to access SQL Server on the Server machine, you must confi

6. If one or both

Groups: SQL Server lets you grant permissions to user groups as well as individuals. Therefore, you might choose to use the above procedure to grant permissions

their systems to prevent POP3 and/or

- Under Application Development Features, you need both ASP.NET 3.5 *and*

- No encryption. In this case, login names and passwords will be sent in plain text

1.

Note:

instances, 68, 87
MainBoiseWeb5-97
International support, 46
Internet secur(t)-3(y)30(, 97)] TJ ET BT 1 0 0 1 189.14 665.98 Tm [( )] TJ ET EMC /P <</MCI